



ISOMETRIC VIEW



SECTION A-A




SECTION B-B
NRCP JOINT DETAIL

NON-REINFORCED PIPE SPECIFICATIONS							
PIPE I.D. (Nominal)	WALL THICKNESS	NRCP CLASS	BARREL O.D.	BELL O.D.	JOINT DEPTH	CORED HOLE	WEIGHT PER PIECE
12"	2¼"	3	16½"	20"	3½"	20"	960 lb
15"	2¼"	3	19½"	23⅞"	3½"	22"	1080 lb
18"	2½"	3	23"	27⅝"	3¾"	26"	1552 lb
21"	3"	3	27"	31¾"	3¾"	30"	1920 lb
24"	3"	2	30"	35⅝"	3⅞"	32"	2336 lb
27"	4"	3	35"	38"	4"	39"	2842 lb
30"	4¼"	3	38½"	41¼"	5¼"	41"	3940 lb
36"	4¾"	3	45½"	49½"	5⅝"	48"	4872 lb

NOTES:

1. CONFORMS TO CURRENT ASTM C14 REQUIREMENTS.
2. CUSTOM FITTINGS ALSO AVAILABLE.
3. MANUFACTURED USING TYPE III/V CEMENT WHICH MEETS THE REQUIREMENTS FOR BOTH TYPE III AND TYPE V CEMENT.
4. LAY LENGTH FOR ALL SIZES = 8.00'
AVERAGE JOINT GAP = 0.04' (½")

 GENEVA PIPE <small>Concrete products. concrete reliability</small>	SHEET: 12"-36" NON-REINFORCED CONCRETE PIPE		
	SCALE:	N.T.S.	DRAWN: RMP
	DATE:	3-1-2013	PROJECT #:
PROJECT: STANDARD DRAWING			
LOCATION: SALT LAKE - OREM - ST. GEORGE			1 of 1